

VIVAX
METROTECH

vLoc3-MLA

Technical Specifications V1.0



Worldwide Locations

World Headquarters, United State of America

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 800-638-7682
Tel : +1-408-962-9990
Fax : +1-408-734-1799
Email : service@vxmt.com
Website : www.vivax-metrotech.com

Central/South America and the Caribbean

Ventas para América Latina

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 800-624-6210
Tel : +1-408-734-1400
Tel : +1-408-734-1400
Website : www.vivax-metrotech.com
Email : VentasparaAmericaLatina@vxmt.com

Canada

Vivax Canada Inc.

41 Courtland Ave Unit 6, Vaughan, ON L4K 3T3, Canada

Tel : +1-289-846-3010
Fax : +1-905-752-0214
Website : www.vivax-metrotech.com
Email : CanadianSales@vxmt.com

United Kingdom

Vivax-Metrotech Ltd.

Unit 18-19, Woodside Road, South Marston Industrial Estate, Swindon, SN3 4WA, UK

Free Phone: 0800 0281811
Tel : +44(0)1793 822679
Email : salesUK@vxmt.com

Australia

Vivax-Metrotech AUS

Unit 1, 176 South Creek Rd, Cromer, NSW, Australia 2099

Tel : +61 2 9972 9244
Fax : +61 2 9972 9433
Website : www.vivax-metrotech.com.au
Email : sales@vxmtaus.com

Germany

Metrotech Vertriebs GmbHAm steinernen Kreuz 10a
D-96110 Schesslitz

Tel : +49 954 277 227 43
Email : serviceGermany@vxmt.com

A. Typical Applications

Item	Parameter
Description	Plug-and-play adapter for the purpose of locating buried EMS markers
Uses	<ul style="list-style-type: none"> - Detection of any one of nine marker ball types, in good conditions, buried to a depth of 6ft (2m) - Detection of large flat markers to a depth of 9ft (3m)

B. Characteristics

Item	Parameter
Construction	High impact ABS injection molded housing
Weight	1.76lbs (0.8kg)
Dimensions	8.2in(L) x 6.2in(W) x 4.0in(H) (208mm x 157mm x 102mm)
Display Type	Per vLoc3 series receiver being used
MLA Antennas	1 x marker transmit antenna, 1 x marker receiver antenna
Power	Provided by vLoc3 series receiver being used
Environmental	IP65 and NEMA 4
External Connectors	8-Pin male plug goes into the vLoc3 series receivers
Temperature Range	<ul style="list-style-type: none"> - Operating: -4°F to 122°F (-20°C to 50°C) - Storage: -40°F to 140°F (-40°C to 60°C)
Approvals	<ul style="list-style-type: none"> - Complies with European standard CE (Directive 99/5/EC) <ul style="list-style-type: none"> • EN 55011 • EN 61000-4-2: A1 & A2 • EN 61000-4-3 • EN 61000-4-8: A1 • ETSI EN 300 330-2 • ETSI EN 301 489-1 • ETSI EN 301 489-3 - Complies with FCC Rules Part 15 <ul style="list-style-type: none"> • CFR 47 part 2 • CFR 47 Part 15

Standard Accessories	<ul style="list-style-type: none"> - Cable organizer - Quick Guide
-----------------------------	--

C. Operational

Item	Parameter																														
Information Displayed on host vLoc3 Series Receivers	<ul style="list-style-type: none"> - Marker reference number and icon - Response to marker ball - Circular bar graph and variable pitch tone to indicate signal strength - Manual EMS (Electronic Marker System) gain control - Proportional left/right indication - Compass: full 360°-line direction indicator - Plug and play automatic recognition of accessories - Gain level (in dB) - Frequency selected - Battery condition - Speaker volume - Operating frequency - Bluetooth and GPS status - Configuration menu & submenus - User definable start-up screen 																														
Operating Frequencies Pre-defined Marker Ball Frequencies	<p>Frequency list defined below:</p> <table border="1"> <thead> <tr> <th>Ref #</th> <th>Utility</th> <th>Frequency (Hz)</th> </tr> </thead> <tbody> <tr><td>1</td><td>Power (Red)</td><td>169,800</td></tr> <tr><td>2</td><td>Water (Blue)</td><td>145,700</td></tr> <tr><td>3</td><td>Sanitary (Green)</td><td>121,600</td></tr> <tr><td>4</td><td>Telephone (Orange)</td><td>101,400</td></tr> <tr><td>5</td><td>Gas (Yellow)</td><td>83,000</td></tr> <tr><td>6</td><td>CATV (Orange/Black)</td><td>77,000</td></tr> <tr><td>7</td><td>Non-potable Water (Purple)</td><td>66,350</td></tr> <tr><td>8</td><td>EDF (French Power) (natural)</td><td>40,000</td></tr> <tr><td>9</td><td>Power Europe (Blue/Red)</td><td>134,000</td></tr> </tbody> </table> <p>***Note: #9 – some markets only***</p>	Ref #	Utility	Frequency (Hz)	1	Power (Red)	169,800	2	Water (Blue)	145,700	3	Sanitary (Green)	121,600	4	Telephone (Orange)	101,400	5	Gas (Yellow)	83,000	6	CATV (Orange/Black)	77,000	7	Non-potable Water (Purple)	66,350	8	EDF (French Power) (natural)	40,000	9	Power Europe (Blue/Red)	134,000
Ref #	Utility	Frequency (Hz)																													
1	Power (Red)	169,800																													
2	Water (Blue)	145,700																													
3	Sanitary (Green)	121,600																													
4	Telephone (Orange)	101,400																													
5	Gas (Yellow)	83,000																													
6	CATV (Orange/Black)	77,000																													
7	Non-potable Water (Purple)	66,350																													
8	EDF (French Power) (natural)	40,000																													
9	Power Europe (Blue/Red)	134,000																													
Operating Modes	<ul style="list-style-type: none"> - Line Location Receiver - Marker Locator - Dual mode operation: Peak response combined with Marker-Ball Detection 																														
Gain Control	Manual gain using "+" or "-" with one touch to return to center (60% of FSD)																														
Performance in Area of Undistorted Fields	Generally locatable to 6ft (2m) depth																														

Performance Using Single Undistorted Signal Source	Locate pinpointing accuracy in single line locate mode:	<ul style="list-style-type: none"> - Over 9ft (3m) – 5% of depth - Up to 9ft (3m) – 3% of depth
	Depth measurement accuracy:	3% of depth
	Current measurement accuracy:	<ul style="list-style-type: none"> - 5% of actual current – over 9ft (3m) - 3% of actual current – up to 9ft (3m)
	Depth range:	Dependent on strength of signal radiating to locator – generally up to 15ft (5m)
Compatible Receivers	vLoc3-Pro, vLoc3-5000 and vLoc3-9800	

D. Shipping and Packaging

Item	Parameter
Shipping Weight	1.98lbs (0.9kg)
Shipping Dimension	9.3in(L) x 6.7in(W) x 4.1in(H) (235mm x 170mm x 105mm)

E. Warranty

Item	Parameter
Warranty	12 months

Disclaimer: Product and accessory specification and availability information is subject to change without prior notice.